60.12"

48.87"

38.12"

23.12"

10.00"   10.00"   10.00"   10.00"

14.18"   14.18"   14.18"   14.18"

4.06"   4.06"   4.06"   4.06"

Line voltage K.O.   Low Voltage Area   Line voltage K.O.   Low Voltage Area   Line voltage K.O.   Low Voltage Area   Line voltage K.O.   Low Voltage Area

CLCTUB48   CLCTUB36   CLCTUB24   CLCTUB12

CLCTUBxx
DESCRIPTION
The CLCTUBxx is the tub for CLC rated Lighting Automation Panel;
the complete assembly also includes one each of the following:

1. Interior (CLCINTERxxxx)
2. Power Supply (RPWRxxx)
3. Cover (CLCCOVxxSL)

Separating the modules simplifies installation. The tub can be mounted early to allow conduit
installation and rough-in wiring. The interior, which includes the relays and terminations,
simply slides into the tub. The lighting circuits and low voltage control wiring can then be
terminated and the cover installed.

SPECIFICATIONS

DESCRIPTION	Lighting Automation Panel Tub
CATALOG #	CLCTUBxx
OPERATING ENVIRONMENT	0-55°C (32-131F) 0-95% RH, non-condensing. Non-corrosive atmosphere.
CODES	NEMA 1 RATED UL916 Energy Management
Finish	Painted Gray ASA 6-1

Job Name: _____

Page: _____ of _____