QuickServer FS-QS-2X10



fieldserver

Overview

The QuickServer is a high performance, fully configurable, cost effective Building and Industrial Automation gateway for integrators to easily interface devices to networks in commercial buildings and industrial plants.

System integrators world-wide have benefitted from the value of the powerful line of interoperability gateways offered by FieldServer. Now, QuickServer adds to that value by running the same robust FieldServer protocol conversion software on a highly cost effective platform backed by the experience, engineering expertise and proven technical support that integrators have come to expect from FieldServer.

The QuickServer FS-QS-2XX0-F series is available at four different point capacities. Each QuickServer is preloaded with 140 different drivers, such as Modbus, BACnet, SNMP, EtherNet/IP and many more. See page 3 for the complete list.

The FS-QS-20X0-F supports up to 250 points. The FS-QS-22X0-F supports up to 500 points. The FS-QS-21X0-F supports up to 1,000 points. The FS QS 23X0-F supports up to 3,000 points. The FS-QS-24X0-F supports up to 5,000 points.

Every QuickServer includes browser-based tools to make it easy to set-up QuickServer and perform diagnostics including determination of status, network settings, node information, map descriptors and more. The USB flash drive also includes the Discovery utility to determine what FieldServers are on a network.

QuickServer Features and Benefits

- Interface 250-5,000 device points (see Specifications).
- DIN rail mount standard.
- BACnet COV support for fast data communication while reducing the traffic over a BACnet network.
- MSA Grid registration connects your devices to the cloud, allowing secure remote access for diagnostics, monitoring and firmware updates.
- On-board diagnostics allow easy troubleshooting for both serial and Ethernet communications.
- **FieldSafe** adds a wealth of security options, including: web configuration page authentication (self-signed certificates), robust user and password management features.

GUI Modbus TCP/IP SNMP EtherNet/IP Ethernet Ethernet Serial to Serial Serial to Ethernet Ethernet to Ethernet

FieldServer Offers

- Largest protocol driver library in the industry, providing the solution to your integration needs.
- Over 20 years of experience in design and manufacture of building automation gateways with thousands of installations, over 700 translation paths using over 100 protocol drivers.
- Trusted, proven technical support before and after shipment.
- MSA Safety partners with BAS and Fire Alarm Panel manufacturers and trade associations to ensure that the drivers and hardware meet your highest industry expectations.

Accessories

• Optional Accessory Kit includes AC power supply, Ethernet cable, mini-screwdriver and a USB flash drive with all data sheets, manuals, notes, the discovery tool and more.

Field Connections											
		Interface Connections									
		RS-2321	RS-485 ²	RS-422 ³	KNX ⁶	RS-485	M-Bus	Ethernet⁴	LonWorks⁵		
	FS-QS-2X10	1	2					1			
	FS-QS-1X11		1					1	1		
QuickServer	FS-QS-1221	1						1	1		
er	FS-QS-1230		1	1				1			
Ś	FS-QS-1231			1				1	1		
<u>.</u>	FS-QS-1240		1		1			1			
Ju	FS-QS-1241				1			1	1		
Ŭ	FS-QS-1X50					1	1	1			
	FS-QS-1X51						1	1	1		

Hardware Specifications

Communication

Serial (Galvanic Isolation):

1 x RS-485/RS-232 & 1 x RS-485 Baud:9600, 19200, 38400, 57600, 76800 Ethernet: 10/100BaseT, MDIX, DHCP Environment

Operating Temperature: -20 to 70°C (-4 to 158°F) **Relative Humidity:** 10-95% RH non-condensing

Ordering Information

- FS-QS-2010-F: 250 data points
- FS-QS-2210-F: 500 data points
- FS-QS-2110-F: 1,000 data points
- FS-QS-2310-F: 3,000 data points
- FS-QS-2410-F: 5,000 data points

Other

Web configuration On-board diagnostics DIN rail mount included **Construction HxWxD:** 4 x 1.1 x 2.7 in (10.16 x 2.8 x 6.8cm) **Weight:** 0.4 lbs (0.2 Kg) **Power Requirements Input:** 24VAC 0.125A; 9-30VDC 0.25A @12 VDC **Max Power:** 3W

Approvals

CE and FCC Class B & C Part 15 BTL marked and UKCA compliant UL 60950-1 and CAN/CSA C22.2 IC Canada & KC certification RoHS3 and WEEE compliant



- FS-QS-2020-F: 250 data points
- FS-QS-2220-F: 500 data points
- FS-QS-2120-F: 1,000 data points
- FS-QS-2320-F: 3,000 data points
- FS-QS-2420-F: 5,000 data points

Options

The Accessory Kit consists of a power supply, Ethernet cable, screwdriver, DIN rail mount and a USB flash drive that includes all manuals, data sheets, notes and the discovery tool.

FS-8915-38-QS Accessory Kit, 110/220V

Life Safety	Industrial Automation	Building Automation	Cloud	Other
Serial Drivers	Serial Drivers	Serial Drivers	XML Over	Utility
ATMI ACM	Allen Bradley DF1	AO Smith (AINP & PDNP)	HTTP	DNP3 Serial
ATMI TGM	B&B Electronics SDD16	BACnet PTP		DNP3 Ethernet
 EST3 Quickstart (UTC Security) 	Caterpillar M5X	BACnet MS/TP		• TL1
EST3 ECP (UTC Security)	GE MarkIV Speedtronic	Carrier (DataLink and DataPort)		Rail switching
Fike Cheetah ISCAN	GE-SNP	Caterpillar M5X		Hanning & Kahl HCS-
Firecom	GE MarkIV Speedtronic	Cleaver Brooks (CB-Link)		R
• Gamewell - FCI (7100, 7200, E3)	Gardner Denver	Gardner Denver		Genisys
Hochiki FireNet	• J-Bus	Lutron Machine		Data Centers
Hochiki FireNet Plus	Modbus ASCII	McQuay Microtech Open		SNMP Ver 2C
 Honeywell Analytics System 16 & 	Modbus RTU	 MetasysTM N2 by JCI 		
CM4	 Modbus Daniels 	Modbus ASCII		
Honeywell Analytics IR-148 Infratox	Modbus TekAir	Modbus RTU		
Mircom FX2000	 Modbus Omniflow 	Modbus Daniels		
• Notifier 1010/2020	Pneumatic Products ADC	Modbus TekAir		
• Notifier AFP 200/300/400	RussElectric Model 2000	Modbus Omniflow		
Notifier INA	 Setra Digital Pressure 	RussElectric Model 2000		
Notifier Italia AM6000	Gage	• Stulz		
Notifier CEI-ABI	Ethernet Drivers	VeederRoot		
Notifier NCA	Allen Bradley CSP	• VESDA		
Notifier NCA 2	(TCP/IP)	Ethernet Drivers		
Notifier NFS-320	EtherNet/IP	BACnet Ethernet		
Notifier NFS-3030	• GE-EGD	BACnet/IP		
Notifier NFS2-640	• GE-SRTP	Cisco Energywise Endpoint		
Notifier Onyx NFS-640	Modbus TCP/IP	Cisco Energywise Management		
Secutron Model R	Omron FINS	API		
Siemens Fire Safety MXL/XLS/FSI		• Convia		
Silent Knight		C-Cure		
Simplex Grinnell 4100		Modbus TCP/IP		
Simplex Grinnell TFX Minerva		Point Six Wireless		
• VESDA		Schneider Electric Cassia		