## **QuickServer KNX Gateway**





## **Overview**

MSA Safety is a leader in protocol gateways for the building automation industry, enabling system integrators and developers to prepare building automation and process control infrastructures for the future by breaking down protocol barriers.

With the QuickServer KNX Gateway, FieldServer enables data access from KNX networks to devices and networks utilizing open and proprietary protocols such as BACnet, Modbus, LonWorks, Metasys N2 by JCI, SNMP and more. With over 100 protocols available in the extensive FieldServer Driver Library, no other product can connect KNX to more products!



FieldServer is in thousands of installations with over 700 translation paths. These gateways are LonMark certified, BACnet compliant, Metasys N2 compatible and mission-critical tested.

QuickServer is a galvanic-isolated translator device on KNX/TP installations with control and monitoring capabilities. All EIS data types are supported, allowing communication to any kind of KNX devices in the installation, such as temperature sensors, shutters, light switches, actuators, alarms etc.

**MSA Grid - FieldServer Manager** registration connects your devices to the cloud, allowing secure remote access for diagnostics, monitoring, alarming and configuration.

On-board diagnostics allow easy troubleshooting for both serial and Ethernet communications.

**FieldSafe** adds a wealth of security options, including: web configuration page authentication (self-signed certificates), robust user and password management features.

Typical data points supported on the QuickServer with KNX are:

- Switching (EIS1, 1-bit)
- Dimming (EIS2, 4-bit)
- Time (EIS3, 24-bit)
- Date (EIS4, 24-bit)
- Float (EIS5, 16-bit)
- · Value (EIS6, 8-bit)
- Drive Control (EIS7, 1-bit)

- Priority (EIS8, 2-bit)
- Float IEEE (EIS9, 32-bit)
- Counter (EIS10, 16-bit)
- Counter (EIS11, 32-bit)
- Access Control (EIS12, 4-bit)
- ASCII character (EIS13, 7-bit)
- Counter (EIS14, 8-bit)

## The product versions include:

- KNX Gateway: Allows BMS systems to access a KNX network using direct read and write of KNX configured groups.
  This setup does not require the use of ETS4 to configure the QuickServer KNX gateway.
- KNX Device Emulation: Allows third party devices to be recognized as KNX devices.

To ensure total satisfaction with our products, FieldServer emphasizes comprehensive customer service and support. This commitment to the highest level of service extends beyond the sales cycle and throughout the product life cycle.

## **Protocols Available**

Omron Fins BACnet MS/TP LonWorks XML GE-EGD

EtherNet/IP BACnet Ethernet Modbus RTU DNP 3.0 Plus over 100 legacy and Metasys N2 by JCI BACnet/IP Modbus TCP/IP SNMP proprietary protocols

For more information go to MSA Safety's QuickServer Gateway webpage.



Propel Item No: T18408