## CAS 2500-04-UL - BACnetIP Data Client Data Logger and HTTP/XML Server

**Product Data Sheet** 

## CAS2500-04-UL - BACnetIP Data Client

- Collect and log data from BACnetIP Enabled devices.
- View Log and current data using the onboard web server.
- Serves data to other applications using XML or HTTP
- Upload log files for later review.
- Simple and easy to use and configure.



### **Description**

Connects to BACnet IP devices to read data. The data and transactions are logged. The log files are available and can be transferred to other computers. Current data can be monitored by remote systems running applications that can issue HTTP or SOAP/XMP GET requests – such applications can be easily developed by end users. Of course, this data is available using an Internet Browser such as Internet Explorer or Google Chrome. Connection parameters, device parameters and data parameters are configurable.

## Logging

Log records of each Modbus read and response transactions are maintained in the file system. Log record with time stamps of data returned by Modbus devices are maintained in the file system. These files are (zipped) human readable data. Log files can be uploaded to a remote PC

using HTTP. When file space runs low, the data client overwrites older files.

## Data Serving

The current value of any/all data objects reads from the BACnet Devices can be monitored remotely using HTTP or XML by using HTTP GET requests or XML/SOAP requests.

Email: dfs@chipkin.com Website: www.chipkin.com



# CAS 2500-04-UL - BACnetIP Data Client Data Logger and HTTP/XML Server

**Product Data Sheet** 

#### **BACnet IP**

Connect to multiple BACnetIP devices. IP and Address are configurable. Connection port is configurable. Data objects, types and properties are configurable.

### **Device Specifications**

#### **Environmental Parameters**

Operating Temperature: 0 to 70 C Humidity: 5% to 95% (non-condensing)

Dimensions
4.2" x 3.25" x 1"
Power Supply
Power: 5-24VDC

Power Adapter: 60W, VAC 100~240V adapter

Compliance

CE, FCC UL and ULc approved

RoHS, Lead-Free

**Interfaces** 

1xRS485 Port

1xRS232 (Debug Port)

1xMicros SD Card

1x 10/100/1000 RJ45 Network

#### Memory/Operation

2MBytes flash memory, 8MBytes of SDRAM

LEDs: Link, Speed/Data, Power

Case

Aluminum with textured paint

# CAS 2500-04-UL - BACnetIP Data Client Data Logger and HTTP/XML Server

**Product Data Sheet** 

## **Connection Configurations**

